

FIG. 2






FIG. 3A




IN CASE OF BD (WHEN BLUE WAVELENGTH IS USED)

FIG. 3B



IN CASE OF DVD (WHEN RED WAVELENGTH IS USED)

FIG. 3C







FIG. 4A

•	DIFFRACTION EFFICIENCY [%]		GRATING DEPTH
	0th-ORDER LIGHT	± 1st−ORDER LIGHT	D[].
BLUE (405nm)	100	0	3
RED (660nm)	41	26	1.89
INFRARED (780nm)	3	41	1.60


DIFFRACTION EFFICIENCY [%]

FIG. 4B




REFRACTIVE INDEX:

n405 : 1.619 n660 : 1.580 n780 : 1.574








DOCKET NO.: 8048-1187 INVENTOR: MASAKAZU OGASAWARA ET AL. FILING DATE: SEPTEMBER 21, 2006 TITLE: OPTICAL PICKUP


5/21

<u>30b</u>

FIG. 6



r≒ APERTURE DIAMETER * 0.7





Focus Error=(A1+A3) - (A2+A4) RF = A1+A2+A3+A4 SPHERICAL ABERRATION = (B1+B3) - (B2+B4)







ABERRATION 1 8.0 0.6 0.4 0.2 0 -0.2 -0.4 -0.6 -0.8 -1 0.08 0.09 0.11 0.12 COVER LAYER THICKNESS [mm]







IN CASE OF BD (WHEN BLUE WAVELENGTH IS USED)







	DIFFRACTION EFFICIENCY [%]		GRATING DEPTH
	0th-ORDER LIGHT	1st-ORDER LIGHT	D[\(\)]
BLUE (405nm)	90	5	14.1
RED (660nm)	93	3	8.1
INFRARED (780nm)) 4	62	6.8



10/21




FIG. 12B





FIG. 13B



IN CASE OF DVD (WHEN RED WAVELENGTH IS USED)





FIG. 14



	DIFFRACTION EFFICIENCY [%]		GRATING DEPTH
	0th-ORDER LIGHT	± 1st-ORDER LIGHT	D[\(\)]
BLUE (405nm)	80	10	5.2
RED (660nm)	98	1	. 3
INFRARED (780nm)	2 .	41	2.5






FIG. 15A


14/21



DOCKET NO.: 8048-1187 INVENTOR: MASAKAZU OGASAWARA ET AL. FILING DATE: SEPTEMBER 21, 2006 TITLE: OPTICAL PICKUP

15/21










FIG. 17



DIFFRACTION EFFICIENCY [%]

	0th-ORDER LIGHT	± 1st-ORDER LIGHT	GRATING DEPTH D[λ]
BLUE (405nm)	84	5	1.1
RED (660nm)	21	33	0.66
INFRARED (780nm)	2	41	0.55






FIG. 18E

DOCKET NO.: 8048-1187 INVENTOR: MASAKAZU OGASAWARA ET AL. FILING DATE: SEPTEMBER 21, 2006 TITLE: OPTICAL PICKUP

19/21





FIG. 19A

FIG. 19B






FIG. 20A




FIG. 20B





FIG. 20C



	DIFFRACTION EFFICIENCY [%]		GRATING DEPTH
	Oth-ORDER LIGHT	± 1st-ORDER LIGHT	D[\(\)]
BLUE (405nm)	100	. 0	3
RED (660nm)	41	26	1.89
INFRARED (780nm)	3	41	1.60

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☑ BLACK BORDERS
☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
☐ FADED TEXT OR DRAWING
☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
☐ SKEWED/SLANTED IMAGES
☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
☐ GRAY SCALE DOCUMENTS
☐ LINES OR MARKS ON ORIGINAL DOCUMENT
☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
□ OTHER.

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.